TORNADO®

TORUS 1660-2 HORSE FENCE

Overview

Tornado's Torus 1660-2 Horse Fence has pre-stripped ends for ease of joining. It features solid vertical wires and closely spaced (2") vertical stay wires to help prevent damage to hooves. The additional 3 horizontal line wires and extra 12" in height compared with the 1348-2 specification make this an ideal solution where a taller horse net is required. The unobtrusive high pressure bonded Torus stiff stay knot does not have any sharp edges, helping to prevent damage to manes, tails, or expensive rugs. Tornado Torus Horse Fence is manufactured with high tensile wire which strains tighter than mild steel and so requires fewer intermediate posts, making it quicker to erect. It does not stretch with weathering so does not need to be retightened annually.

Compliance with North American Standards

- Manufactured to ASTM 116
- Class 3 zinc galvanised coating meets or exceeds ASTM A641

Sustainability

All Tornado products are 100% recyclable.

Traceability

This fence is batch marked and can be traced back to point of manufacture.

Installation Guidelines

A straining post is required at every major change in direction or any termination and should be supported by a strut or box assembly. Netting should be tied off on the straining posts by hand or with suitable joiners. When tensioning the fence the 'crimp' in the net should be reduced by approximately 50%. Avoid driving staples tight against the wire as this will damage the galvanised coating. Tornado Torus Horse Fence can be enhanced by a single strand of Centaur Lightning electric fencing to add additional height and visibility.

Health and Safety

It is recommended that safety gloves, boots and glasses are worn at all times when handling the product.

Suitable for

Horses

Specification

No. of horizontal line wires	16
Overall height (inches)	60
Distance between vertical wires (inches)	2
Top & bottom line wire specification	12.5g - 179 - 201 ksi
Intermediate line wire specification	12.5g - 179 - 201 ksi
Vertical stay wire specification	12.5g - 100 - 123 ksi
Average weight per 100 ft roll (lbs)	191
Material composition	Class 3 heavily galvanised steel wire

All measurements are approximate. It is the user's responsibility to check the product is suitable for the application. We reserve the right to change specifications without notification.



TORUS 1660-2 HORSE FENCE

